6 CR

INFORMATION REPORT INFORMATION REPORT

CENTRAL INTELLIGENCE AGENCY

This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorised person is prohibited by law.

S_F_C_D	<u></u> m		50X1-HUM
Rumania	REPOR	<u></u>	
Sodium Products Plant No. 1 at	DATE DISTR.	3 May 1961	
marporar lie de perudina	NO. PAGES	. 4	
(perior box c 'm)	REFERENCES	RD	
			50X1-HUM
			50X1-HUM
	Rumania Sodium Products Plant No. 1 at Ocna Muresului (production)	Sodium Products Plant No. 1 at DATE DISTR. Ocna Muresului (production processing No. PAGES There or not to the Induding No. PAGES	Rumania REPOR Sodium Products Plant No. 1 at DATE DISTR. 3 May 1961 Ocna Muresului (production, processing No. PAGES 14

- 1. Sodium Products Plant No. 1 occupies the premises of the former Solvay plant in Ocna Muresului and is subordinate to the Rumanian Ministry for 2 the Petroleum and Chemical Industries. It was greatly expanded and developed between 1955 and 1960 by the addition of new buildings and the installation of East German equipment. Whereas the total production in 1948 was 50,000 tons, the plant is to produce about 240,000 tons of calcined soda and 60,000 tons of caustic soda in 1961.
- 2. At the end of 1960, the plant employed about 800 permanent employees, of whom some 38 were engineers, and about 3,000 temporary workers occupied in work connected with the plant's expansion. According to the plans, the plant will finally employ a maximum of 1,000 permanent workers. It now works three shifts every day of the year, Sundays and holidays included.
- 3. The plant has the following production departments:
 - a. Lime kilns department
 - b. Slaking vats

5432

- c. Compressors department.
- d. Refining by absorption department (Distilare Absorbere)
- e. Department for refining brine solution by decantation (Distilare Saramura Decantata)
- f. Rotary filters department



25

1. Modaly liliters department

S-E-C-R-E-T

50X1-HUM

STATE X ARMY X NAVY X AIR X NSA X OCR

(Note: Washington distribution indicated by "X"; Field distribution by "#".)

S-E-C-R-E-T 50X1-HUM

- g. Rotary calcinators department
- h. Caustic soda department (also used for calcined soda production)
- i. Evaporation department
- j. Concentration department
- k. Pumps department
- 1. Refrigeration department.
- 4. Both calcined soda and caustic soda are produced by the Solvay method.
 The procedures for the production of each are as follows:
 - Calcined soda: The raw material, dolomite from the Turda quarries, is placed in lime kilns. The kilns burn coke; experiments in replacing the coke with methane gas have not yet succeeded. From the kilns the lime passes into the slaking vats and becomes milk of lime. The carbon dioxide given off in the kilns passes into the compressors department where it is put under pressures gradually raised to 13 atmospheres. residue from the dolomite goes to the department for refining brine solution by decantation. The milk of lime is refined by absorption and mixed with brine solution in the department. Ammonia is then added in preparation for producing sodium bicarbonate. The liquid is then charged with carbon from the compressors department, and unrefined sodium bicarbonate is obtained. The water from the unrefined product is removed in rotary filters run by vacuum pumps, and the sodium bicarbonate which remains is channeled through troughs onto conveyor belts which carry it to rotary calcinators to be heated and dried at 850 to 1,000°C. The produce obtained after calcination is sodium carbonate. The sodium carbonate is pumped by Fuller pumps to elevators to be gradually cooled, and is then weighed automatically into sacks. The sacks whose contents are of a quality suitable for export are transferred to a special export warehouse: the others are for the home market. The soda is exported to North Korea, and, in small quantities, to East China 50X1-HUM Germany.

50X1-HUM

b. Caustic soda: The milk of lime passes from the vats to the "decarbonatoare"
and then to the decantation section of the caustic soda production department where the residue is removed. The clear lime solution continues on to the evaporation department to be dried by superheating. The soda is taken to the concentration department, transformed into a 200-percent solution, and automatically weighed into metal barrels, which are taken by conveyors to the caustic soda warehouse.

- 5. The plant is surrounded by a concrete wall about 2.5 meters high, in which there are four gates: Gate No. 1 is used by the plant's directorate and engineers and by visitors, No. 2 by the MONCHIM workers who are employed in enlarging the plant, No. 3 by the trains, and No. 4 by the workers, clerks and technicians of the plant. The old buildings are made of brick with tiled walls; the new ones are also of brick but on metal construction.
- 6. The plant's thermal power station produces 22 megawatts, but since the plant requires only 6.5 megawatts, the surplus is automatically transferred to the nearby provincial power station at Ocna Muresului. The plant's station produces high tension current at 35 and 6 kilovolts, which two transformers step-down to alternating current at 380 volts for the equipment, and 220 volts for illumination. Its equipment includes:

S-E-C-R-E-T

		\$_F_C_F_F_T			5074 11118
					50X1-HUM
		- 3 -			
				-	50X1-HUM
a.	Three Babcock-Wilcox- the Lang-Ganz plant i		of 45 tons,	each produced	р у
b.	One 45-ton Babcock-Wi	.lcox-type steam boil	Ler produced	l at the Mao T	se Tung
c.	One 40 cubic meter	boiler.			50X1-HUM
d.	One 11-megawatt turbiduced by the Lang-Gar		ssure of 13	atmospheres,	pro-
e.	One Brown-Bovery turk	oine, possibly driver	n by the	boiler.	50X1-HUM
f.	Two 4.5 megawatt Resi	ta boilers, now bein	ng installed	i.	

- 7. Other structures at the plant are the following:
 - a. A single-story building, about 25 by 10 meters in size, containing a large laboratory for chemical analysis and a laboratory for research into sodium and chlorine compounds.
 - b. A single-story building, about 40 by 10 meters in size, housing the maintenance workshops for electrical and mechanical repairs and the carpentry shop. Among the machinery are 14 or 15 lathes produced at the Iosif Ranghet plant in Arad.
 - c. An old pumping station for pumping water from the Mures River.
 - d. The department for refining brine solution is in a 15 by 12 meter building containing six 1,500 cubic meter tanks. The solution is piped into the department in pressurized pipes, some above ground and others underground, made of steel and of F-250 and F-350 cast iron.
 - e. A decanting tank for the water for the power station, with a capacity of 1,200 cubic meters.
 - f. A pumping station for the above tanks.
 - g. A water tower and the tower's pumping station.
 - h. The director's home, a small, single-story building.
 - i. A pumping station for the 24 refrigeration columns. About 4,500 cubic meters of water passes through each column per hour.
 - j. A building containing five large pumps which pump 1,500 cubic meters per hour from the Mures River into the decanting tanks by means of pressure pumps at four atmospheres pressure. Only three or four pumps work simultaneously.
 - k. The funicular railroad stations and the railroad stores.
 - Six lime kilns, each with a production capacity of 200 cubic meters per day.
 - m. Decenting tanks.
 - n. Slaking vats.
 - o. Towers for the purification of carbon dioxide. They are now in disuse having been replaced by venturi pipes shaped thusly: ()

S-F-C-R-F-T	• •

	Saniti	ed Copy Approved for Release	2011/04/28 : CIA-RDP80T	JUZ46AU589UUZ500(JT-T
•			m		
			S-E-C-R-E-T		50X1-HUN
			- 4 -		7
			-		
	p•	Department for exploiting kilns.	the dolomite and coke	ashes remaining i	n the
	q.	Compressors department con products of Ganz-Lang, one			o are
	r.	Columns for the refining o	f ammonia by absorptic	n.	
	5•	18 columns for producing c 1.8 meters in diameter, an under the original managem corrosion by a new system	d has an output of 40 ent). The columns are	tons (as against protected agains	20 tons
	t.	A building containing 8 ro	tary filters and vacuu	m pumps.	
	u•	A building containing 8 roeach with a capacity of 15			onal);
	v.	Warehouse for soda destine	d for export.		
	W•	Warehouse for soda, approx	imately 20 meters squa	re and 40 meters	high.
	x.	Two-story office building,	25 by 8 meters in siz	e•	
	у•	Department for the product carbonate crystals, and so			.um
	Z•	The old boiler department, department for the product	now used as a mainter ion of sodium bicarbor	ance shop for the	e above
	aa.	Department for the product volfatita (sic).	ion of silica gel thro	ugh the use of	
	bb.	Various workshops (coopera	ge, maintenance, etc.	, and stores.	
	cc.	Workers quarters.			50X1-HUM
8.	0cna	Muresului with a legend sh	arge sketch of Sodium owing the layout of th	Products Plant No e installation.	0. 1 at
					50X1-H
			S-E-C-R-E-T		

Sanitized Conv	Approved for Rela	2011/04/28	· CIA_PDD80T002	46A058900250001-1
Samuzed Copy	Approved for Rei	3ase 20 1/04/20 .	. CIA-RDP001002	40AU303UUZ3UUU 1- 1

Legend

1. To Ocna Muresului. 2. Salt mines, exploited to a depth of 150 meters. 3. Salt mines, exploited by surface dissolution. 50X1-HUM

- 4. Tobacco factory.
- 5. Offices of the Ocns Muresului salt mines.
- 6. Vicara railroad station.
- 7. Workers' quarters of Sodium Products Plant No. 1.
- 7a. Restaurant.
- 7b. Technical department and library.
- 8. Gate No. 4 (for workers, technicisms and clerks).
- 9. Chimney.
- 10. Caustic sods warehouse.
- 11. Concentration department.
- 12. Shop producing metal barrels.
- 13. Evaporation department.
- 14. Becantation department.
- 15. Silica gel department.
- 16. Administrative personnel's housing.
- Nos. 17 to 24 Power station of the plant
- 17. Six-kilowatt transformer unit.
- 18. Control room.
- 18a. 4.5-megawatt Resita boiler.
- 19. 11-megawatt Ganz-Lang turbine.
- 20. 40-cubic-meter Velox boiler.
- 21. 4.5-megawatt Resita boiler.
- 22. Three Ganz-Lang boilers and one boiler from the Mao Tso
 Tung (Bucharest) Plant.

C	PART	

ACIO

23. Pumping station.

50X1-HUM

- 24. Water preparation installations.
- 24a. Stores.
- 25. Old boiler room, now a workshop.
- 26. Chimney, approximately 45 meters high.
- 27. Gate No. 3 (for trains).
- 28. Gate No. 2 (for Monchim employees).
- 29. Chimney.
- 30. Department for the production of sodium bicarbonate and sodium silicate refined from soda crystals (soda cristalizata).
- 31. Gate No. 1 (for the management, engineers, and guests).
- 32. Offices.
- 33. Rew materials stores.
- 34. Workers quarters.
- 35. Workers quarters.
- 36. Eight rotary calcinators.
- 37. Eight rotary filters.
- 38. 18 columns for the production of carbonates.
- 39. Department for the refining of ammonia by absorption.
- 40. Compressors department.
- 41. Slaking vats.
- 42. Electrically-powered moist filters.
- 43. Carbon dioxide purification towers (no longer used)
- 44. Venturi pipes for purifying carbon dioxide.

- 45. Ventilation equipment for the kilns.
- 46. Lime kilns.
- 47. Decantation tanks.
- 48. Station No. 19 of the funicular railroad.
- Hos. 49-52 High-pressure pumping station for supplying water for the refrigeration columns.
- 49. Water decentation tanks.
- 50. Chamber for 4- and 6-kilovolt pumpingunits (uncertain).
- 51. Magnesium oxide chamber (uncertain).
- 52. Five pumps.
- 53. Coke bins.
- 54. Limestone bins.
- 55. Pumping station and three tanks of water.
- 56. Ocna Muresului provincial power station.
- 57. Pumping station "A".
- 58. Pumping station "A".
- 59. Mures River.
- 60. To Rabolemi
- 61. Station No. 17 of fundcular railroad.
- 62. Station No. 18 of funicular railroad.
- 63. Director's home
- 64. Tower for potable water.
- 65. Pumps for supplying water to the decantation water.
- 66. Decantation tanks.
- 67. Department for refining brine solution.

OTHER.

Sanitized Copy Appr	oved for Release	2011/04/28:	CIA-RDP80T00246A058900250001-1	50X1-HUN
	010410110000		00 (1 (D) 00 1 00 2 10 (100 00 00 00 2 00 00 1 1)	

- 11 -

- 68. Pumping station.
- 69. Maintenance workshops.
- 70. Laboratories.

